

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: LINKS FOR CONFIGURING A VIRTUAL PRIVATE NETWORK

APPLICANT: MATTHEW W. POISSON
MELISSA L. DESROCHES
JAMES M. MILILLO

"EXPRESS MAIL" Mailing Label Number EL182578382

Date of Deposit April 2, 1999

I hereby certify under 37 CFR 1.10 that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office To Addressee" with sufficient postage on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Alison Brazil
Alison Brazil

LINKS FOR CONFIGURING A VIRTUAL PRIVATE NETWORK

Background

5 This invention relates particularly to providing links for configuring a virtual private network.

 LANs (Local Area Networks), Intranets, and other private networks interconnect user computers, file servers, e-mail servers, databases, and other resources. Typically, organizations want to offer remote access to private network resources to traveling employees, employees working at home, and branch offices without compromising the security of the private network.

 Virtual private networks (a.k.a. Extranets) securely stitch together remote private networks and remote computers using a public network such as the Internet as a communication medium. Each private network can connect to the public network via an extranet switch such as the Contivity™ Extranet switch offered by Nortel™ Networks. Extranet switches provide a variety of virtual private network functions such as network packet tunneling and authentication.

 For configuring the functions provided by the switch, Contivity™ switches offer a web-server and web-pages programmed to configure the different virtual private network functions in response to administrator interaction with the web-pages. By using a browser to navigate to each virtual private network switch, one after another, the administrator can configure the tunneling, authentication, packet filtering, and other functions provided by the switch. Management functions provided by the Contivity™ switches are described in greater detail in the New Oak™ Communications Extranet Access Switch Administrator's Guide.

Summary of the Invention

In general, in one aspect, a method of managing a virtual private network includes providing a graphical user interface configured to display at least one link for each
5 of a plurality of computers offering virtual private network functions.

Embodiments may include one or more of the following features. The computers may be extranet switches. The links may be HTTP (HyperText Transfer Protocol) links. The
10 links may link to information describing users of the virtual private network functions provided by the computers, packet filters provided by the computers, and/or computer access hours. The method may further include transmitting an HTTP request in response to selection of a link.

15 The method may further include providing a list of the computers offering virtual private network functions in the same display as a link. The link displayed may correspond to a computer selected from the list of computers offering virtual private network functions.

20 In general, in another aspect, a method of managing a virtual private network includes providing a graphical user interface display that includes a list of extranet switches offering virtual private network functions, and a collection of HTTP links for an extranet switch selected
25 from the list, the links causing transmission of an HTTP request.

In general, in another aspect, the invention features a computer program product, disposed on a computer readable
30 medium, for managing a virtual private network. The program

includes instructions for causing a processor to provide a graphical user interface configured to display at least one link for each of a plurality of computers offering virtual private network functions.

5 In general, in another aspect, the invention features a computer program product, disposed on a computer readable medium, for managing a virtual private network. The program includes instructions for causing a processor to provide a graphical user interface display that includes a
10 list of extranet switches offering virtual private network functions, and a collection of HTTP links for an extranet switch selected from the list, the links causing transmission of an HTTP request.

Advantages may include one or more of the following.

15 By providing links corresponding to different computers providing virtual private network functions, an administrator can quickly access a desired page on any particular computer. The administrator can also quickly access the same page (e.g., the users page) on a variety of
20 different switches, one after another. Additionally, the links obviate the need to remember the different URLs of the different computers offering virtual private network functions.

Other advantages of the invention will become
25 apparent in view of the following description, including the figures, and the claims.

Brief Description of the Drawings

FIG. 1 is a diagram illustrating bulk configuration
30 of multiple extranet switches.

FIG. 2 is a diagram of tunnels provided by configured extranet switches.

FIG. 3 is a flow-chart of a process for bulk configuring multiple extranet switches.

5 FIG. 4 is a diagram of a switch manager exporting configuration information to multiple extranet switches.

FIGS. 5-13 are screenshots of a wizard that guides an administrator through a bulk configuration process

FIG. 14 is a diagram illustrating importing
10 information from multiple extranet switches.

FIG. 15 is a diagram of a switch manager importing information from an extranet switch.

FIGS. 16-20 are screenshots of extranet switch reports.

15 FIGS. 21-31 are screenshots of a graphical user interface that enables an administrator to manage extranet switches in a virtual private network.

FIG. 32 is a screenshot of a menu of links to web-pages offered by an extranet switch.

20 FIGS. 33-39 are screenshots of web-pages offered by an extranet switch.

Description of the Preferred Embodiments

25

Introduction

An extranet switch manager provides administrators with a tool that centralizes management of different extranet switches in a virtual private network. The manager
30 can bulk configure multiple extranet switches, prepare

reports describing the extranet switches, provide convenient access to individual switch configuration mechanisms, and provide an intuitive representation of virtual private network elements. The manager offers these capabilities to an administrator via an easy to use graphical user interface (GUI). After an administrator enters IP (Internet Protocol) addresses of extranet switches in a virtual private network, the switch manager can quickly import and export data to both view the current configuration and activity of the switches and quickly alter the configuration of one or more switches.

Bulk Configuration of Multiple Extranet Switches

As shown in FIG. 1, a virtual private network 102 can include private networks 106, 110 and/or remote computers 114 that communicate over a public network 104. Each private network 106, 110 can connect to the public network 104 via an extranet switch 100a, 100b such as a Contivity™ Extranet Switch offered by Nortel Networks. As shown, each extranet switch 100a, 100b has a private interface that communicates with a private network 106, 110 and a public interface that communicates with the public network 104. Extranet switches 100a, 100b handle virtual private network functions such as network packet tunneling and authentication. The extranet switches 100a, 100b can also enforce packet filtering rules, enforce hours of access, and perform other functions that maintain a secure virtual private network. Many of these functions may be included in a firewall or router. Hence, we use the term "extranet switch" to generically refer to a system providing

these functions. As shown in FIG. 1, switch manager instructions 116 reside on a remote computer, however, the instructions 116 could reside on any computer able to communicate with the extranet switches 100a, 100b.

5 Each switch 100a, 110b can provide different tunneling protocols (e.g., PPTP (Point-to-Point Tunneling Protocol), L2F (Layer 2 Forwarding), L2TP (Layer 2 Tunnel Protocol), and IPsec (IP Secure)), different encryption schemes, different authentication mechanisms (e.g., internal
10 or external LDAP (Lightweight Directory Access Protocol) and RADIUS (Remote Authentication Dial-In User Service)), and different packet filtering schemes (e.g., filtering based on the direction of communication, the source and/or destination of a packet, and/or the type of TCP (Transfer
15 Control Protocol) connection established). As shown in FIG. 1, switch manager instructions 116 enable an administrator to quickly configure multiple switches 100a, 100b to share a set of common characteristics (e.g., the same authentication scheme and the same tunneling protocols) by transmitting the
20 same configuration information 118a, 118b to each switch 100a, 100b.

Referring to FIG. 2, after being configured, the virtual private network 102 permits secure communication between private networks 106, 110. For example, a computer
25 112 on a first private network 110 can securely send network packets to a computer 108 on a second private network 106 by tunneling 120 through the public network 104. An extranet switch 100a receiving a packet prior to transmission over the public network 104 can provide a tunnel 120 by
30 encrypting and/or encapsulating the network packet.

Encryption encodes packet contents to prevent computers on the public network from reading the original contents. Encapsulation generates a new packet addressed to the extranet switch 100b at the end of the tunnel 120 and
5 includes the original packet as the contents of the new packet. By analogy, encapsulation is like placing a mail envelope in a bigger envelope with a different mail address. Encapsulation prevents computers on the public network 104 from identifying the addresses of private network 106, 110
10 resources.

When the extranet switch 100b at the end of the tunnel 120 receives a packet, the extranet switch 100b can decrypt and de-encapsulate the packet for delivery to its destination 108. The second extranet switch 100b can also
15 authenticate information received from the first extranet switch 100b to make sure a would-be intruder is not masquerading as a member of the virtual private network 102.

As shown, a switch 100a can also provide tunnels for a remote user 114 connected to the public network 104. For
20 example, an employee can access private network 110 resources by connecting to an ISP (Internet Service Provider) and establishing a tunnel 122 with an extranet switch 100a. Again, the extranet switch 100a can authenticate the identity of the remote user 114 to prevent
25 unauthorized access to the private network 110.

The extranet switch 100a can also connect tunnels. For example, if so configured, the switch could connect 124
tunnels 120 and 122 to enable the remote user 114 to also access resources on private network 106 via tunnels 122 and
30 120.

Referring to FIG. 3, switch manager instructions 116 receive 126 information specifying the configuration of multiple extranet switches. The bulk configuration information can be specified by a user, provided by a
5 program that automatically configures switches, or copied from configuration information of a previously configured switch. After receiving 126 the configuration information, the switch manager instructions 116 transmit 128 data and/or instructions corresponding to the received configuration
10 information to the extranet switches. Each extranet switch processes 130a, 130b the transmitted information to change its configuration in accordance with the transmitted information.

Referring to FIG. 4, an extranet switch 100a, 100b
15 includes software and/or firmware instructions 130a, 130b that handle switch functions. Such functions can include authentication 132a, tunnel management 134a, packet filtering 136a, etc. Each switch 100a, 100b can also include a script interface 138a that processes script
20 commands. For example, a script command of "call omSET using ("trustedFTPenabled" "ENABLED")" configures the switch to allow processing of FTP (File Transfer Protocol) requests from trusted computers.

In one implementation, switch manager instructions
25 116 include instructions for a graphical user interface 144 (GUI), a script interface 140, and configuration 142 instructions that model the extranet switches and coordinate the exchange of information between the GUI 144 and the script interface 140. When a user specifies bulk
30 configuration information via the GUI 146, the script

interface 142 produces a script 118a, 118b that includes script commands for configuring the switches in accordance with the user specified information. Appendix A includes a sample configuring script. In the implementation described
5 above, the switch manager 116 can export the configuration information 118a, 118b to extranet switches by transmitting the information 118a, 118b to a pre-determined switch directory via FTP (File Transfer Protocol). The script interface 138a, 138b on the switches 100a, 100b detect and
10 process the script upon its arrival.

The exporting technique described above is merely illustrative and a wide variety of other techniques could be used to coordinate communication between a computer executing switch manager instructions 116 and the different
15 extranet switches 100a, 100b. For example, the communication need not use FTP nor need the information take the form of a script.

Referring to FIG. 5, the GUI provides a wizard (e.g., Bulk Configure Extranet Switches) that enables an
20 administrator to bulk configure multiple extranet switches by interacting with a preprogrammed series of dialogs. The dialogs query an administrator for different sets of switch characteristics. The preprogrammed set of dialogs reduces the chances an administrator will forget to configure a
25 particular set of switch characteristics.

Referring to FIG. 6, after invoking the bulk configuration wizard, an administrator can select one or more extranet switches to bulk configure. The manager will transmit configuration information only to the selected
30 switches.

Referring to FIG. 7, the wizard permits an administrator to configure the selected switches to provide an account to a particular administrator. Since a single administrator may be in charge of all the switches in a virtual private network, establishment of an identical administrator account on the different switches enables the administrator to quickly login to the different switches using the same id and password.

Referring to FIG. 8, each switch may be individually configured to have a unique hostname (e.g., "NOC2000"). An administrator can bulk configure different switches to have the same DNS (domain name service) domain such as "myVPN.com". By defining a common domain for multiple switches, an administrator can thereafter refer to a particular switch by combining the domain name and the hostname (e.g., "myVPN.com/NOC2000"). Primary and backup DNS servers can translate the domain and hostname to a particular IP (Internet Protocol) address. Thus, by specifying a common domain, the administrator can identify a switch by a memorable text entry instead of a more cryptic IP address (e.g., "255.255.68.28").

Referring to FIG. 9, an administrator can configure the services offered by the switches. For example, the administrator can enable or disable different tunnel protocols (e.g., IPsec, PPTP, LT2P, and L2F). The GUI also gives the administrator the ability to enable or disable tunneling sessions initiated from within the private network served by a switch and tunneling sessions initiated from a source outside the private network (e.g., "public" tunnels).

The administrator can also enable or disable different communication protocols such as HTTP (HyperText Transfer Protocol), SNMP (Simple Network Management Protocol), FTP (File Transfer Protocol), and TELNET.

5 Additionally, the manager gives the administrator the ability to control the types of communication allowed. For example, an administrator can enable or disable tunnels between two extranet switches (e.g., branch to branch communication), between two users tunneling to the same
10 switch (e.g., end user to end user), and between a user and a branch office tunneling to the same switch.

Referring to FIG. 10, an administrator can bulk configure the SNMP traps reported by the switches and the host computers that will receive notification of the traps.
15 SNMP traps allow an administrator to react to events that need attention or that might lead to problems. The switches allow the scripting of SNMP alerts so that a combination of system variables can signal an SNMP trap. The GUI permits the administrator to not only enable or disable different
20 types of traps, but also to provide the interval between execution of the SNMP scripts.

Referring to FIG. 11, an administrator can also configure RADIUS accounting performed by each selected switch. RADIUS is a distributed security system that uses
25 an authentication server to verify dial-up connection attributes and authenticate connections. RADIUS accounting logs sessions with records containing detailed connection statistics. The administrator can enable and disable RADIUS accounting, configure the switches to use internal or
30 external RADIUS servers, and specify how frequently RADIUS

records are stored. By configuring the switches in a virtual private network to use the same RADIUS accounting methods, switch usage and access can be easily compared between the different switches.

5 Referring to FIG. 12, if enabled, an administrator can bulk configure the type of RADIUS authentication performed by the switches. For example, as shown, the switches can offer AXENT (AXENT OmniGuard/Defender), SecurID (Security Dynamics SecurID), MS-CHAP (Microsoft Challenge
10 Handshake Authentication Protocol encrypted), CHAP (Challenge Handshake Authentication Protocol), and/or PAP (Password Authentication Protocol) authentication.

The administrator can also define a primary RADIUS server and one or more alternate servers. The primary
15 server receives all RADIUS authentication inquiries unless it is out of service. In the event that the Primary Server is unreachable, the Switch will query the alternate RADIUS servers. By bulk configuring the servers used to provide RADIUS authentication, administrators can quickly route all
20 RADIUS authentication requests to the same collection of RADIUS servers.

Referring to FIG. 13, switches may use LDAP authentication in addition to or in lieu of RADIUS authentication. An external LDAP Server such as the
25 Netscape Directory Server can store remote access profiles. The switch queries the LDAP Server for access profile information when a user attempts to establish a tunnel connection. The Master LDAP Server is the primary server to process queries. Should the Master server become
30 unavailable, the switch attempts to initiate a connection

with the Slave servers. Bulk configuring different switches to use the same LDAP servers both eases the burden of switch management on the administrator and reduces the likelihood the administrator will inadvertently specify a different
5 LDAP hierarchy on different switches.

After completing the bulk configuration wizard, the manager stores the specified configuration information, but does not transmit the information until the administrator specifically exports the configuration data. This provides
10 administrators with a safeguard against accidentally bulk configuring the switches with unintended characteristics.

Reporting Capabilities

Referring to FIG. 14, in addition to configuring
15 multiple extranet switches 100a, 100b, switch manager instructions 116 can also produce reports describing the extranet switches 100a, 100b in a virtual private network 102. As shown, the extranet switches 100a, 100b can transmit configuration, capacity, and activity information
20 for inclusion in a report.

Referring to FIG. 15, switch manager instructions 116 can transmit a script 152a, 152b that includes script commands requesting current switch 100a, 100b information. For example, a script command of "call omGET using
25 ("security.trustedFTPenabled")" requests information describing whether an extranet switch 100a, 100b is currently configured to accept FTP (File Transfer Protocol) requests from a trusted computer. Appendix B includes a sample script requesting information from a Contivity™
30 switch.

The switch 100a, 100b script interface 138a, 138b processes the script commands 128 and produces a file 150a, 150b including the requested information. The script interface 138a, 138b on the switch 100a, 100b can store the
5 file in a pre-determined directory. The switch manager instructions 116 can then use FTP to retrieve the information 150a, 150b.

Again, a wide variety of other techniques could enable the switches 100a, 100b to communicate with the
10 switch manager instructions 116. Additionally, instead of the request/response model described above, the switches 100a, 100b could schedule periodic execution of a script and/or periodic transmission of the switch information 150a, 150b.

15 Referring to FIG. 16, the switch manager GUI can provide a menu of different reports that can be produced for selected extranet switches. The manager prepares the report by analyzing and/or including data imported from the different extranet switches.

20 Referring to FIG. 17, a first report can display different static attributes of the selected switches such as DNS details.

Referring to FIG. 18, a security report displays the security configurations of the selected switches such as the
25 enabling/disabling of different tunneling and communication protocols. The security report can also list changes made to the selected switch configurations when such changes occurred (not shown). The report can also include information summarizing failed access attempts to the
30 switches (not shown). This report enables an administrator

to quickly view the different security configurations and any troublesome security statistics.

Referring to FIG. 19, a capacity report shows the current total capacity of tunnels that selected switches can provide and the total number of subscribers and/or users configured to use the switch. This report provides a simple but useful gauge of tunnel capacity. Based on the capacity report, an administrator can decide whether to add more subscribers to an available tunnel pool or to increase the size of tunnel pool, for example, by upgrading or adding an extranet switch.

Referring to FIG. 20, a trending report displays the number of tunnels for each tunnel technology provided by the different extranet switches over a user-specified amount of time. The report allows subscribers to select any number of currently defined switches or services.

Custom Views

Referring to FIG. 21, the switch manager GUI eases administration of a virtual private network extranet switches by collecting information about the entire network in a single display. As shown, the switch manager GUI displays configuration information imported from one or more extranet switches (e.g., via the import mechanism described in conjunction with FIG. 15). The GUI uses a split screen display that includes a navigation pane listing different virtual private network switches, subscribers, and other information such as periodic scheduling of management functions and scripts that can perform these functions. As shown, the listing uses a hierarchical

tree to display the virtual private network elements. An administrator can view a listed element in more detail by expanding the tree (e.g., clicking on the "-" or "+" next to an element). The tree display enables an administrator to quickly find, add, remove, and configure different virtual private network extranet switches.

As shown, the display also provides a tabbed dialog control 210 that provides more information and management options for a virtual private network element currently selected in the navigation pane 200 (e.g., "Configuration Data" 212). The control 210 includes dialogs for adding new elements to the tree from a palette 214 of elements, for viewing and altering properties 216 of a selected element, for a list of wizards 218 that perform tasks frequently used with a selected element, and a list of network links 222 that enable an administrator to manually configure an individual extranet switch. By providing management options corresponding to an element selected in the navigation pane 200, the GUI presents only a relevant subset of a wide variety of different management features at a given moment.

Referring to FIGS. 22-26, the GUI enables an administrator to quickly view and modify the configuration of any particular switch in the virtual private network from within a single application. For example, as shown, an administrator can quickly add a new subscriber 226 to the virtual private network. Briefly, a subscriber is any entity that uses a virtual private network service (e.g., a tunnel protocol). For example, service providers typically use the same extranet switch to provide virtual private network services to different organizations. In this case,

each organization could be considered a subscriber.
Subscribers can also be individual users.

As shown in FIG. 22, after selecting the
"Configuration Data" element 212, a palette tab presents
5 different elements that can be added to the selected virtual
private network element 212. A new subscriber 226 can be
added by dragging-and-dropping the subscriber 224 palette
tool onto the "Configuration Data" element 212. As shown in
FIG. 23, the administrator can rename the new subscriber
10 226. As shown in FIG. 24, by selecting the new subscriber
226, selecting the "palette" tab 214, and dragging a "VPN
Service" 228 (e.g., a tunnel) from the palette onto the new
subscriber 226, the administrator can also configure a
switch or switches to offer a particular tunneling protocol.

15

As shown in FIG. 25, the administrator can name the
tunnel, define the tunneling technology used by the tunnel
(e.g., L2TP), and enter the tunnel starting and ending
points which, as shown, are extranet switches.

20 As shown in FIG. 26, after configuring different
subscribers and switches, the GUI provides an administrator
with a variety of different methods of looking at a virtual
private network. For example, as shown, by expanding a
subscriber 232 an administrator can quickly see shortcuts to
25 the extranet switches 236, 238 offering tunnels for
subscriber use. Alternatively, as shown in FIG. 27, the
administrator can view the tunneling technologies offered by
a particular switch 240 by using the navigation pane 200 to
select the switch's tunnel element 242. The properties

dialog 244 displays the configuration of the different tunneling technologies.

The different presentations of the data (e.g., subscriber based and switch based) described above enable
5 the administrator to both ensure that subscribers are adequately served and that individual switches are configured as desired.

Referring to FIGS. 28-29, the process described above (i.e., selecting an element from the tree and using
10 the tabbed dialog to view and modify the element's characteristics) can be used to configure a variety of virtual private network characteristics. For example, by selecting a switch 240 from the navigation pane 200, the administrator can view and modify the switch's 240
15 characteristics. As shown in FIG. 28, an administrator can add RADIUS Authentication 244 to a switch 240 by dragging-and-dropping the RADIUS Authentication Server palette selection 242 onto the selected switch 240. As shown in FIG. 29, the administrator can then set different
20 RADIUS authentication settings for the switch 244. An administrator can use a similar technique to add and/or configure SNMP (Simple Network Management Protocol) settings, switch interfaces to private and/or public networks, Ethernet settings, IPX (Internetwork Packet
25 Exchange) settings, and other extranet switch features displayed in the switch palette. Appendix C includes screenshots of the different palette elements and their properties that can be used to configure an extranet switch.

The alterations to the switches, for example, adding
30 RADIUS authentication to a switch, while immediately

represented to the administrator, is not exported until explicitly requested by the administrator. Again, this gives the administrator a chance to avoid unintended modifications.

5 Referring to FIGS. 30-31, beyond viewing and modifying switch characteristics, an administrator can use the GUI to organize information for easy access and identification of different elements. For example, as shown in FIG. 30, an administrator can drag a folder 250 from the
10 palette onto an element. The administrator can rename the dragged folder 252 (e.g., to "Subscribers") and drag-and-drop different subscribers into the folder 252. As shown in FIG. 31, a similar technique enables an administrator to organize different switches into different
15 groupings such as switches using LDAP 254 for authentication and switches using RADIUS 256.

Integrated Access to a Switch's Configuration Mechanisms

As previously described, an extranet switch such as
20 the Contivity™ switch can include a web-server and different network pages (e.g., HTML (HyperText Markup Language) documents) that enable an administrator to individually configure an extranet switch. By navigating to a switch web-server, an administrator can view and/or modify a
25 switch's configuration.

Referring to FIG. 32, the GUI can present a menu 260
of network links (e.g., link 268) to web-pages offered by a selected extranet switch 270. As shown, the menu 260 includes a description of the link 272 and a corresponding
30 URL (Universal Resource Locator) identifying a web-page

offered by a switch. As shown, the URL includes designation of a communication protocol (e.g., HTTP (HyperText Transfer Protocol) 262, an IP address 264, and the location of a particular page at the specified IP address 268. When a
5 user selects a link from the menu 260, the switch manager can transmit an HTTP request for the selected URL. Alternately, the switch manager can instantiate or call a network browser and pass the selected URL. The GUI prepares each URL in the menu 260 by prepending a switch's IP address
10 264 to a predefined set of web-page locations 266.

By providing the link menu in conjunction with the navigation pane 200, administrators can quickly access a desired page on any particular switch and can also quickly access the same page (e.g., the users page) on a variety of
15 different switches, one after another. Additionally, the menu 260 obviates the need to remember the different extranet switch URLs or expend the time needed to navigate through any menu provided by the switch itself which necessitates potentially long waits for information to be
20 transmitted to the switch manager.

As shown, the web-pages include pages that control how a switch handles users (FIG. 33), branch offices (FIG. 34), packet filters (FIG. 35), groups of users (FIG. 36), access hours (FIG. 37), and other information such as a menu
25 that tailors a web-based configuration session (FIG. 39). Descriptions of the functions of these different web-pages is described in the New Oak Communications Extranet Access Switch Administrators Guide, pages 82-138 of which are incorporated by reference herein.

Other Embodiments

The embodiments described above should not be considered limiting. For example, one of skill in the art could quickly construct a switch manager that perform the
5 functions described above using different GUI controls or a different arrangement of GUI controls.

Additionally, the techniques described here are not limited to any particular hardware or software configuration; they may find applicability in any computing
10 or processing environment. The techniques may be implemented in hardware or software, or a combination of the two. Preferably, the techniques are implemented in computer programs executing on programmable computers that each include a processor, a storage medium readable by the
15 processor (including volatile and non-volatile memory and/or storage elements), at least one input device, and one or more output devices. Program code is applied to data entered using the input device to perform the functions described and to generate output information. The output
20 information is applied to one or more output devices.

Each program is preferably implemented in a high level procedural or object oriented programming language to communicate with a computer system. however, the programs can be implemented in assembly or machine language, if
25 desired. In any case, the language may be a compiled or interpreted language.

Each such computer program is preferable stored on a storage medium or device (e.g., CD-ROM, hard disk or magnetic diskette) that is readable by a general or special
30 purpose programmable computer for configuring and operating

the computer when the storage medium or device is read by the computer to perform the procedures described in this document. The system may also be considered to be implemented as a computer-readable storage medium, 5 configured with a computer program, where the storage medium so configured causes a computer to operate in a specific and predefined manner.

Other embodiments are within the scope of the following claims.